



Micro Quadlock AMP 3-polig/6-polig

Produktmerkmale

- Passend zum Winkelsensor 424RA
- Unterschiedliche Pin-Belegungen verfügbar

Technische Zeichnung

BILD 1/3

L0.D.0.B




BILD 2/3

L0FD...B

female AMP
Micro Quadlock




L0ZD...B

female AMP
Micro Quadlock




BILD 3/3

L0FD...B



L0ZD...B



Produktoptionen

BILD 1/1

ORDERING KEY

L0				Micro Quadlock AMP
	FD			6-pin
	ZD			3-pin
		0		Sheath material PVC, grey
		1		Sheath material PUR, black
			01B	Cable length 1m ± 30mm
			03B	Cable length 3m ± 40mm
			05B	Cable length 5m ± 60mm
			00B	Cable length 10m ± 80mm
				Other cable materials and cable lengths on request

Artikel-Merkmale

Attribute	L0FD0..B	L0FD1..B	L0ZD0..B	L0ZD1..B
Kabelmaterial	PVC	PUR	PVC	PUR
Betriebstemperatur min.	-40 °C	-30 °C		-20 °C
Betriebstemperatur max.	80 °C		105 °C	80 °C
Lagertemperatur min.	-40 °C	-30 °C		-20 °C
Lagertemperatur max.	80 °C		105 °C	80 °C
Steckertyp	AMP Quadlock 1-967616-1 socket			
Kabellänge	10 m			
Kabeldurchmesser	7,5 mm	8,2 +/-0,25 mm	6,2 +/-0,2 mm	5,7 +/-0,2 mm
Polanzahl	6			
Litzenanzahl	6		3	
Litzenquerschnitt	0,75 mm²			