

Suction pipe S

With level monitoring Configuration

Material of suction pipe	
☐	PVC
☐	PP

Float	
☐	PVC hollow part Ø 37x35
☐	PP foamed Ø 30x35
☐	PP hollow part Ø 37x35

Cable material	
☐	PVC
☐	PUR

Cable length	
☐	1 m
☐	3 m
☐	5 m
☐	10 m

Connections/outlets		Suction hose material
☐	5/8" UNF external thread	PE
☐	5/8" UNF external thread With 1/8" inner thread	
☐	Hose connection, 1 m hose	PE or PTFE
☐	Hose connection, 3 m hose	
☐	Hose connection, 5 m hose	
☐	Hose connection, 10 m hose	

Seal	
☐	FKM (Viton)
☐	EPDM
☐	PTFE

Contact form (with falling level)	
☐	1 switching point: bottom N.O. (A), 48V
☐	1 switching point: bottom N.C. (B), 48V
☐	1 switching point: bottom changeover contact (C), 48V
☐	1 switching point: bottom N.O. (A), 250V
☐	1 switching point: bottom N.C. (B), 250V
☐	2 switching points: 2x N.O. (A), 48V
☐	2 switching points: 2x N.C. (B), 48V
☐	2 switching points: bottom N.O. (A), top N.C. (B), 48V
☐	2 switching points: bottom N.C. (B), top N.O. (A), 48V

Optional accessories	
☐	Set of brackets
☐	Hose connection set
☐	Color-coding

Valve ball	
☐	Glass
☐	PTFE
☐	Steel
☐	Ceramic
☐	Without

Nominal length _____ (min. 220... max. 1200 mm - 10 mm increments)

