



## Universal Switch 151U...A

Universal switch 151 U.. ..A with two switching levels for operation of the turn signal, horn and headlamp-flash functions.

The Steering column switch 151 U can be used in agricultural vehicles, construction machinery and self-propelled machinery. Using proven technology, these steering column switches are robust and reliable even under tough working conditions.

### Technical specifications

- Space-saving design
- Various actuation types: no-detent/detent actuation
- Temperature range -30 °C to +80 °C
- Optionally with large handle (Ø17 mm) or flat handle (24 x 38 mm)

## Technical drawing

IMAGE 1/2



IMAGE 2/2



## Product options

IMAGE 1/1

### ORDERING KEY

151 U						Universal switch
						<b>Function</b>
	N					No detent
	M					Detent
						<b>Lever version</b>
		S				Standard lever, diameter 7 mm
						<b>Handle version</b>
			1	0	B	Small handle, handle print for turn signal / horn / headlamp flasher (three switching levels)
			1	1	A	Small handle, handle print for turn signal / horn (two switching levels)
			1	2	A	Small handle, without handle print (two switching levels)
			1	2	B	Small handle, without handle print (three switching levels)

## Article characteristics

Attribute	151UM.A..	151UN.A..	ED151UM.A..	ED151UN.A..
Contact form	mechanical		-	
Turn signal - max. switching voltage	12 V DC	48 V DC	-	
Turn signal - max. switching current	8 A	0.5 A	-	
Turn signal - max. switching power	96 W	10 W	-	
Contact form - turn signal	mechanical	Reed Switch	-	
Horn - max. switching voltage	12 V DC		-	
Horn - max. switching current	4.2 A		-	
Headlamp flasher - max. switching voltage	12 V DC		-	
Headlamp flasher - max. switching current	0.256 A		-	
Headlamp flasher - max. switching power	inductive 3 W		-	
Horn max. inductive switching power	50 W		-	
Deflection - turn signal	± 15 °		-	
Deflection - headlamp flasher	5 °		-	
Operating temperature min.	-30 °C		-	
Max. operating temperature	80 °C		-	
Min. storage temperature	-40 °C		-	
Max. storage temperature	80 °C		-	
Installation depth	45 mm		-	