



## eloProg - Controlador de segurança modular programável - Módulo fieldbus

Conexão direta ao CLP da máquina através de módulos fieldbus.

Até 1 módulo fieldbus pode ser conectado ao módulo básico por meio de conector T montado na parte traseira do módulo. Status é exibido por meio de LEDs na parte frontal.

- Todos os protocolos de comunicação fieldbus disponíveis no mercado
- Endereços selecionáveis via barramento
- Conexão por barramento reduz o tempo de montagem e espaço no painel de controle
- Diferentes taxas de transmissão dependendo do protocolo fieldbus selecionado
- Conector T pré-montado (barramento de 5 vias) para conexão ao módulo básico simplifica a fiação e economiza espaço no painel de controle

Desenho técnico

IMAGE 1/1



## Product options

IMAGE 1/1

### ORDERING KEY

485	EPF			Fieldbus module
		PD		Profibus DP
		DN		DeviceNet
		CO		CANopen
		EI		Ethernet IP
		EI	2	2x Ethernet IP
		EC		EtherCAT
		PN		PROFINET
		PN	2	2x PROFINET
		UB		Universal-Serial-Bus
		MR		Modbus RTU
		MT		Modbus TCP

## Características do artigo

Attribute	485EPFCO	485EPFDN	485EPFEC	485EPFEI	485EPFEI2	485EPFMR ▶
Transmission rate	max. 1 MBit/s	125 kBit/s 250 kBit/	–	100 MBit/s		–
Operating voltage min.	19.2 V DC					
Operating voltage max.	28.8 V DC					
LED display	two-coloured					
Fieldbus system	CANopen	DeviceNet	EtherCat	Ethernet IP	2x Ethernet IP	Modbus RTU
Selectable station address	0...125	0...63	Depending on the configuration			
Dimensions	108 x 22,5 x 114,5 mm (H/B/T)					
Housing material	PA					
Housing colour	grau					
Protection class, housing	IP20 DIN EN 60529					
Operating temperature min.	-10 °C					
Max. operating temperature	55 °C					
Min. storage temperature	-20 °C					
Max. storage temperature	85 °C					
Relative humidity	10...95 %					
Mounting type	Mounting rail					
Weight	150 g					
Torque for connection terminals	0.6 N m					
Connection present on PC	yes					
Connection to base module	proprietary 5-way bus (T-connector)					
Screw terminals	yes					
Pluggable connection terminals	yes					
Min. connection cross section	0.5 mm²					
Max. connection cross section	2.5 mm²					
Certified in accordance with	UL 508 / CSA 22.2					

Attribute	485EPFMT	485EPFPD	485EPFUB
Transmission rate	–	12 MBit/s	–
Operating voltage min.	19.2 V DC		
Operating voltage max.	28.8 V DC		
LED display	two-coloured		
Fieldbus system	Modbus TCP	Profibus DP	USB interface module
Selectable station address	Depending on the configuration	1...127	Depending on the configuration
Dimensions	108 x 22,5 x 114,5 mm (H/B/T)		
Housing material	PA		
Housing colour	grau		
Protection class, housing	IP20 DIN EN 60529		
Operating temperature min.	-10 °C		
Max. operating temperature	55 °C		
Min. storage temperature	-20 °C		
Max. storage temperature	85 °C		
Relative humidity	10...95 %		
Mounting type	Mounting rail		
Weight	150 g		
Torque for connection terminals	0.6 N m		
Connection present on PC	yes		
Connection to base module	proprietary 5-way bus (T-connector)		
Screw terminals	yes		
Pluggable connection terminals	yes		
Min. connection cross section	0.5 mm <sup>2</sup>		
Max. connection cross section	2.5 mm <sup>2</sup>		
Certified in accordance with	UL 508 / CSA 22.2		